



**Stablaire** Liquid LPG Pump Packages; Models: BS1 through BS3 (5-110 GPM)



- Fully packaged liquid pressure stabilization system specifically designed to match ASDI's complete line of vaporization and air/gas mixing equipment.
- Complete with bypass line, pressure relief valve, shut-off valves, check valve, and pressure gauges.
- An inlet strainer is provided for field installation.
- Pump motors through 10HP are fitted with manual starters; 15HP and above have magnetic starters.
  STABILAIRE<sup>®</sup> pump systems are factory piped, wired, and tested.
- System designed to meeet Class I, Division 1, Group D requirements.



## **Specifications**

							Pui	mp Se	lectio	n Cha	rt												
Pump Model		Millions of BTU's Per Hour															System						
		7	14	21	28	42	56	70	84	100	125	150	175	200	225	250	Pressure						
BS1 -	1HP																						
BS1¼ - 2	2HP																						
BS1¼ -	3HP																5 & 8 PSI Venturi System 100 PSID						
BS1½ -	3HP																						
BS2 -	5HP																						
BS2 - 7 1	½ <b>HP</b>																						
BS3 - 1	0HP																						
BS1 -	1HP																						
BS1¼ -	3HP																10 PSI Venturi System 125 PSID						
BS1¼ -	5HP																						
BS1½ -	5HP																						
BS2 -	5HP																						
BS1 -	1HP																						
BS1¼ -	3HP																12 PSI Venturi System 150 PSID						
BS1¼ -	5HP																						
BS1½ -	5HP																						
BS2 - 71	½ <b>HP</b>																						
BS2 - 1	0HP																						
BS3 - 1	5HP																						
BS3 - 2	20HP																						

This chart is based on the manufacturer's recommendation of sizing the pump for 2 to 2½ times the actual flow required except for the SC series which do not share this requirement.

# Features/Options

- These positive displacement systems use rotary vane pumps with a built-in over pressure relief valve, designed for continuous use with high reliability.
- A back pressure control valve provides stable delivery pressure by returning excess pump capacity to the storage tank.
- Each system is supplied with an explosion proof motor and start/stop station installed to meet Class I, Division 1, Group D requirements.
- Magnetic starters available for the smaller pumps.
- The ecomony operation includes a magnetic starter and pressure switch to minimize the amount of time the pump is in operation reducing wear and tear and saving electricity.

### **Belt Driven Pump**



### **Direct Drive Pump**



### Side Channel Pump



STABILAIRE® is a registered U.S. trademark of Algas-SDI.



#### Home Office:

1140 NW 46th Street PO Box 70498 Seattle, Washington 98107 USA

Tel: 206.789.5410 Fax: 206.789.5414

e-mail: sales@algas-sdi.com internet: www.algas-sdi.com

#### **Mexico Office:**

Bosque de Alisos number 47-A 5 Piso Col. Bosques de las Lomas Mexico D.F. 05120

Tel: 52.5261.8100 Fax: 52.5259.8085

e-mail: algas-sdi@cft.com.mx

#### **Beijing Office:**

Room A1007 Huibin Office Building No. 8 Beichen Dong St. Chaoyang District, Beijing 100101, P.R.C.

Tel: 86.10.64969593, 64993818 Fax: 86.10.64969592, 64993817

e-mail: algasbj@public.east.cn.net

### Your ASDI distributor:

ECLIPSE Innovative Thermal Solutions Algas • SDI Form: S0401